

## GLX 494 PRIM

### ACRYLIC PRIMER FOR ORGANIC COATS

#### DESCRIPTION

**GLX 494 Prim** is an acrylic based coat primer for the acrylic coats and paints of Thrakon.

#### SUBSTRATE

**GLX 494 Prim** is applied on concrete, mortars, veneer bases and painted surfaces.

#### PRELIMINARY WORK

Prior to its application **GLX 494 Prim** is diluted with 25% clean water.

#### APPLICATION

**GLX 494 Prim** is applied on one layer. In case of high temperatures and high substrate absorbency, a second layer can be applied.

#### PRACTICAL ADVICE

- **GLX 494 Prim** is applied with roller or spraying.
- The application of the product during rain or frost must be avoided.
- The product is durable against rain 24 hours after application.
- Any spatters must be cleaned with water immediately.
- The ambient temperature during the application must be above +5°C.
- **GLX 494 Prim** must be completely dried before the application of coats or paints.

#### CONSUMPTION

Approximately 0,20 - 0.25 kg/m<sup>2</sup> (4-5kg/m<sup>2</sup>).

#### PACKAGING – STORAGE

The **GLX 494 Prim** product is maintained for 1 year sealed in dry storage spaces and in temperature above 0 °C.

#### PRECAUTIONS

Protect the eyes and skin. In case of contact rinse with plenty of water. In case of contact with eyes seek medical advice immediately. Read the information on the label and in the Technical

Leaflet of the product before use. Wear appropriate protective clothing and gloves. The product's Safety Sheet is available to professionals upon request.

TECHNICAL CHARACTERISTICS	UNITS	STANDARD	VALUE
Appearance			Liquid solution
Determination of density	(kg/l)	EN 2811-1	1,58±0,04
Viscosity	(cps)	Brookfield	14.000-20.000
Consumption per layer	(Kg/m <sup>2</sup> )		0,20-0,25

*Note:* The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50 % and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

*The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.*