

## PRIMO PROFESSIONAL HYBRID EMULSION PAINT ANTIMICROBIAL



### DESCRIPTION

**PRIMO PROFESSIONAL** is an acrylic paint of excellent antimicrobial action, specially formulated for professional indoor and outdoor use. It provides easy application, strong hiding power and high efficiency. It prevents the penetration of microbes into the film and is recommended for application in indoor areas with problems of fungi and bacteria pollution.

Specially designed for professional use, it is suitable for areas requiring frequent painting and freshening, as public buildings, schools, hospitals, hotels, stairwells, storage rooms, ceilings, and surfaces soiled with graffiti, etc. It is odourless and completely friendly for the user and the environment.

### APPLICATION

Suitable for internal and external application in all usual building surfaces such as walls, plaster, concrete, bricks,

ceilings, gypsum boards, etc.

### ADVANTAGES - FEATURES

- Product environmentally friendly.
- Odorless
- Does not contain ammonia.
- Surfaces with excellent breathability.
- Excellent resistance to sunlight.
- Excellent coverage.
- Strong adhesion.
- Suitable for areas that require frequent painting and freshening.
- Excellent workability
- Ideal combination of economy and performance.

### SUBSTRATE PREPARATION

The surface must necessarily be clean, dry, sound and free from dust, mould, grease before applying. Remove all frayed or peeling old paint. Where necessary grouting, use the **STATUS 100% ACRYLIC PUTTY** and after drying, rub with sandpaper and dust well. Where there are large cracks, use putty **STATUS ONE COVER**, with a single pass without rubbing. On new surfaces, apply a first layer of **STATUS ACRYLIC PRIMER**,

or **STATUS AQUADUR**. If it is fresh plaster or cement, let it dry absolutely thoroughly for at least one month before painting. On gypsum boards, soiled surfaces or surfaces previously painted with low quality paints, first apply **STATUS DUR**.

### APPLICATION

Stir thoroughly before use, dilute properly (5-10%) and apply 1-2 coats of paint. Apply the second layer at least 2-3 hours after the first. Close well after application. It can be stored in tightly closed container without any problem for a long time only if it has not been diluted.

The painted surfaces is recommended not to be washed until 20-30 days have passed after the paint application. On fresh plaster or cement, leave to dry completely for at least one month before applying.

## DRYING

Dries out in 1-2 hours (touch-free).

## RECOATABILITY

Recoat after 2-3 hours, depending on the temperature and humidity of the environment. Drying times are related to standard weather conditions (25°C, 60% humidity). These can be changed under different weather conditions.

## COLOURS

It is offered in white and in thousand shades through the painting system of STATUS.

## CONSUMPTION

10-12 m<sup>2</sup> / lt, depending on the texture and porosity of the surface.

## TOOLS APPLICATION

Brush, roller, or airless spray gun.

## CLEANING TOOL

Immediately after use, drain thoroughly the paint inside the container and clean all tools with hot water and soap. Do not empty washings into the watercourses.

## PACKAGING

Available in plastic containers of 3 lt, 9 lt, 16 lt.

## STORAGE

It can be stored in tightly closed original container without any problem for a long time only if it has not been diluted. Store in a cool and dry place.

## VOLATILE ORGANIC COMPOUNDS (VOC)

- Class : (a) Interior matt walls and ceilings (gloss <25@60°) (WB)
- V.O.C limit : 30 gr/lt
- Maximum V.O.C of product ready to use : 29 gr/lt

## APPLICATION TEMPERATURE

Do not apply in temperatures below 10°C or before rain. During application surface should not come in direct exposure to solar radiation. Adverse conditions during or

immediately after application may affect the final properties of the product.

# PRIMO PROFESSIONAL HYBRID EMULSION PAINT ANTIMICROBIAL



## PRECAUTIONS

For information on the safe use, storage and disposal of the product read the text on the label and in the most recent MSDS. MSDS is available upon request to the professionals. The paint leftovers should not be disposed with household

waste. You should seek advice from local authorities on the disposal and collection of waste.

Poisons Information Centre Tel. 210 77.93.777

TECHNICAL CHARACTERISTICS	UNITS	STANDARD	PRICE
Density (20°C)	(g/ml)	EN ISO 2811.01-02	1,62 ± 0,03
Viscosity	(cps)	Brookfield	26400-29600
pH		ISO 976-96	8-9
Gloss (60°)		EN ISO 2813-99	< 7
Dilution with water	(% v/v)	-	5-10