

STATUS MONOSIS OUT COOL ACRYLIC EMULSION PAINT



DESCRIPTION

STATUS MONOSIS OUT is a special, water soluble, top quality cool paint, suitable for exterior use. It is a pioneering insulation system specially designed for providing top quality reflectance, resistance to water and remarkable energy-saving performance. It perfectly insulates exterior walls and covers the cracks. The special glass beads it contains divert solar radiation, thus securing lower indoor temperature in the summer, while they prevent heat from escaping in the winter. However,

the most important feature is energy-saving performance. Recommended for all exterior surfaces, balconies, flat roofs and ceilings. Highly resistant, it is the ideal solution for country houses or hotels, where exterior walls are more often liable to fading due to harsh weather conditions. High coverage and durability. It insulates exterior walls from humidity, does not stain, is waterproof, breathes and is easily applied. Thanks to its long lifespan the interior of the house will look recently painted for many years to come.

APPLICATION FIELDS

Suitable for exterior use. Perfectly insulates exterior walls and covers the cracks. Recommended for all exterior surfaces, balconies, flat roofs and ceilings. Highly resistant, it

is the ideal solution for country houses or hotels, where exterior walls are more often liable to fading due to harsh weather conditions.

ADVANTAGES – CHARACTERISTICS

- Lower indoor temperature in the summer.
- Prevents the loss of heat in the winter.
- Energy-saving performance.
- High coverage.
- Insulates exterior walls from humidity.
- No stains.
- Water-repellent.
- Durable.
- Breathing and easily applied.
- Long lifespan.

SUBSTRATE PREPARATION – APPLICATION

The surface should necessarily be clean, dry, rigid and free from dust, mould and oil before application. Remove all detached or peeled old paints. If stucco is required, use **STATUS 100% ACRYLIC PUTTY** and, after it has dried, sandpaper and dust well. In case of big cracks, apply only one layer of the ready to use **LIGHT, WHITE STATUS ONE COVER** putty, which needs no smoothening. In new surfaces, first apply a layer of **STATUS DUR** or **STATUS AQUADUR**. In case of fresh plaster or cement, let it dry deeply for at least 1

month before painting. The **STATUS MONOSIS OUT** system can be used in already painted surfaces as long as they have been cleaned well and loose parts have been removed. Stir well the content of the container before every use. For longer life, at least 2 layers of paint are recommended. The second layer should be applied at least 4-5 hours after the first. To preserve reflective and water-repelling properties, avoid applying a different plastic or acrylic paint after the application of **STATUS MONOSIS OUT**.

DILUTION

5–15 % with water.

DRYING

Touch dry after 2-3 hours.

RECOATING

Recoat after 4–5 hours. Drying times refer to normal environmental conditions (25°C, humidity 60%). Any difference in environmental temperature and humidity could affect the above times.

APPLICATION RATE

6-8 m²/lt on properly prepared surfaces.

APPLICATION TOOLS

Brush, roller, gun or airless gun.

CLEANING OF TOOLS

Immediately after use empty all the paint into the container and clean the tools with hot water and soap. Do not pour the washing liquids on the ground.

PACKAGING – SHADES

Available in plastic containers of 3 lt and 10 lt.
Available in white.

STORAGE

After application close the container tightly to preserve in good condition for future use. It can be stored in tightly closed containers for a long time as long as it has not been diluted. Store in cool and dry places. Protect from sun and frost.

VOLATILE ORGANIC COMPOUNDS (VOC)

- (c) For exterior walls with mineral substrate (WB)
- VOC limit value: 40 gr/lt
- Maximum VOC content in product ready for use: 39 gr/lt

APPLICATION TEMPERATURE

Avoid painting at temperatures lower than 10°C. Adverse conditions during or shortly after application could affect the final properties of the product.

PRECAUTIONS

For information about safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product, which is available upon request to the professionals.

The remains of the paints should not be disposed of together with domestic waste. Ask for advice from the local government with regard to the disposal and removal of waste.

Poisoning Centre Tel. No.: 210 77.93.777