

DECOR ART PIGMENTS IN LIQUID FORM



DESCRIPTION

DECOR ART is pigment in liquid form with main use mixing with **THRAKON DECOR** microcement. Alternatively (under specific conditions), it can be

mixed with any type of cement based mortars such as coatings, adhesives, sealants.

APPLICATION FIELDS

The fields of application of **DECOR ART** after mixing with microcement **DECOR** vary. (For more information

on application fields see the datasheet of microcement **DECOR**).

ADVANTAGES-CHARACTERISTICS

- Suitable for indoor and outdoor applications.
- Resistant to UV radiation.
- Suitable for permanent immersion in water.
- Easily transported.
- Reduces the stock demands.
- Non-toxic.
- Multiple uses in various structural systems.

APPLICATION

Empty and wash the pigment in the water used to mix the microcement. In this way you ensure that the whole amount of **DECOR ART** is added to the mixture. Stir with an electric mixer until homogeneous. Then empty

the content of the bag in the liquid mixture and stir well to form a workable mix. If this not done in such way it is likely to have discolorations in the final surface.

PACKAGING-STORAGE

Available in plastic bottles (250ml). **DECOR ART** remains unharmed for at least 24 months if protected

from humidity, frost and direct sunlight.

RECOMMENDATIONS

All shades are resistant to UV radiation, however some of them may discolored after applying them permanently outdoors with intense radiation. Mixing colors should

always be done in accordance with the product instructions. In all other cases the different way of mixing is done by the applicator responsibility.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and of the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version