

PAINT REMOVER PAINT REMOVER



DESCRIPTION

REMOVER is a new generation powerful stripping product suitable for the simple and quick removal of old or new enamel paints, primers, varnishes, nitro or oven paints as well as plastic paints. Removes the paint from

any surface such as walls, floors, wood and metal. It does not contain dichloromethane.

AREAS OF APPLICATION

Suitable for removing all types of water or solvent-based paint from any surface such as:

- Enamel
- Primers
- Varnishes
- Nitro or oven paints
- Plastic paints

ADVANTAGES - SPECIFICATIONS

- New generation specially formulated solvents.
- Simple and easy application
- Removes all kinds of paints and varnishes.
- Removes paints from any surface
- Guaranteed result.
- It does not contain dichloromethane.

APPLICATION

Apply a thick layer and cover the entire surface with a brush or roller. When the old paints soften, remove with a spatula. If there is a thick coat of the old paint, a second coat will need to be applied 10-15 min after the first. After paints are removed, the surfaces are cleaned

with a solvent and are ready for painting. Close the container tightly after use to keep the paint in good condition for future use. Can be stored in a tightly sealed container for a long time.

DRYING

Dries in 10-15 minutes.

REQUIRED QUANTITIES

Depending on the surface and the type of paint-varnish used.

TOOLS

Brush, spatula and scraper.

TOOL CLEANING

Clean all tools with **WHITE SPIRIT** immediately after use and then with hot water and detergent. Do not dispose of washing waste water into the aquifer.

PAINT REMOVER PAINT REMOVER



PACKAGING

Available in 375ml, 750ml, 4lt tin cans.

STORAGE

Store original, sealed containers in dry place at temperatures between +5°C and +35°C for a long period of time.

TEMPERATURE

Do not apply when temperatures are below 5°C. Adverse conditions during or shortly after application may affect

the final properties of the product.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining

paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

Poisons Information Call Center 210 77.93.777

TECHICAL SPECIFICATIONS	UNITS	STANDARD	VALUE
Viscosity	(KU)		85±5
Density (20°C)	(g/ml)	EN ISO 2811.01-02	0.975 ± 0.025
Dilution	(%)		Ready-to-use

Note: Measurements are performed in a laboratory environment at a temperature of +23°C, a Relative Humidity (RH) of 50% and without ventilation. Variations are possible depending on the work site conditions, such as temperature, humidity, ventilation and absorbency of the substrate.

The technical information and guidelines in this brochure relating to the application and end-use of Thrakon's products is based on the Company's current expertise and experience on the products and are given in good faith provided they are properly stored, used and applied in accordance with the guidelines given by Thrakon. Given that we are unable to directly inspect the conditions that prevail at the work site as well as the application of the product, the Company shall not provide any guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility, which is based on written information in this brochure, written or oral or otherwise provided recommendations and guidelines. By applying the product in a small area, users are advised to test the product's suitability for the intended application and purpose. Thrakon reserves the right to amend the properties of its products without prior notice. All orders are accepted only after acceptance of the above and under the Company's respective Trade Policy terms. This version of the technical data sheet automatically cancels any previous version.