

## PRIMO ACRYLIC PAINT ACRYLIC COLOR



### DESCRIPTION

The **PRIMO ACRYLIC PAINT** is an aqueous dispersion of acrylic paint for exterior use. Due to the special composition exhibits increased resistance to alkalis and can be applied to concrete surfaces visible but in every kind of cement base surface preceded the proper preparation as well as bricks, stones, wood, mortar, stucco, grout. It protects the steel reinforcement of the elements that cause corrosion as moisture, fumes and rain.

Offers high water-repellency and excellent resistance to adverse atmospheric conditions, industrial and atmospheric pollutants and UV radiation over time. It has strong adhesion to all kinds of old and new surface and maintains its elasticity over time. It has low odor, dries quickly and is absolutely friendly for the user and the environment. Its special formulation provides excellent breathability, high whiteness and resistance to frequent washing and yellowing. Easy to apply, has excellent hiding power and high efficiency.

### APPLICATION

- Suitable for application and protection of alkaline surfaces which have been preceded by adequate preparation such as:
- visible concrete surfaces and in every

kind of cement base surface

- bricks, stones, wood, mortar, stucco, grout

### FEATURES - BENEFITS

- Suitable for application and protection of alkaline surfaces such as bare concrete.
- Protects the steel reinforcement of the elements that cause corrosion as moisture, fumes and rain.
- High water-repellency.
- Excellent resistance to sunlight.
- High resistance to adverse atmospheric conditions.
- High strength industrial and atmospheric

pollutants

Resistant to washing.

- Fast drying
  - Excellent coverage.
  - High whiteness
  - Great Workability
  - High performance
  - Non-yellowing
  - Retains its elasticity
- Low odor

### SUBSTRATE PREPARATION

The surface must necessarily be clean, dry, sound and free from dust, mold, grease before applying. Remove all frayed, or peeling old paint. Where necessary grouting, use the **STATUS 100% ACRYLIC PUTTY** and after drying, rub with sandpaper and dust well. Where there are large cracks, use putty for the ready to use Lightweight, White Stucco **STATUS ONE COVER**, with a single pass without rubbing. On new surfaces, paint a first hand **STATUS ACRYLIC PRIMERS**, or **STATUS DUR**

**WATER.** If it is fresh plaster or cement, let it dry absolutely thoroughly for at least one month before painting. Plasterboard and for repainting hydrocolored surfaces (with lime or glue) or soiled surfaces (nicotine, soot from heaters, soot, fumes, coffee, juice, graffiti, inks, markers, mildew, mold, moisture, oil, etc.), prime first with **STATUS DUR**. Do not ever paint surfaces that may contain moisture. First make sure that the cause of the moisture stopped and that the surface is completely dry.

## APPLICATION

Stir well the contents of the container before use, dilute properly and apply 1-2 coats color. After the second hand at least 2-3 hours after the first. Then close well the container to maintain in good condition for future use. Can be stored in well

sealed container, without any problem for a long time only if it has not been diluted. The paintwork is recommended not to be washed prior to over 20 to 30 days. On new surfaces plaster or concrete paint after 30-40 days.

## DRYING

Dries in 1-2 hours, so as not to touch fairs. Full resistance to washing after 4 weeks.

## RECOATABILITY

Recoated after 2-3 hours. Drying times refer to normal ambient conditions (25 ° C, 60% humidity). Any differences in temperature and humidity of the environment can alter the above times.

## CONSUMPTION

Available in white, gray, terracotta.

## COLORS

10-12 m<sup>2</sup> / lt, depending on the texture and porosity of the surface.

## TOOLS APPLICATION

Brush, roller, or spray gun airless.

## CLEANING TOOL

Immediately after use, drain well the color inside the box and clean all tools with warm water and soap. Do not empty washings into the groundwater.

## PACKAGING

Available in plastic containers of 0,75 lt, 3 lt, 9 lt.

## STORAGE

In the original, sealed packaging in dry environment at temperatures between +5 ° C and +35 ° C for 12 months from the date of production.

## VOLATILE ORGANIC COMPOUNDS (VOC)

• Maximum allowable VOC content (Directive 2004/42/EC) for the product category A / c 'Coatings & exterior walls of mineral substrate, type Y, PHASE II: 40 gr / lt

• Maximum VOC content of the product ready for use: 35 gr / lt

## APPLICATION TEMPERATURE

Do not apply at temperatures below 10 ° C or before rain. In applying the surface should not come in direct exposure to sunlight. Adverse conditions during or immediately after application may affect the final properties of the product.

## NOT RECOMMENDED

- In areas with constant movement
- On surfaces that are constantly under water.

## PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product before the product MSDS is available upon request to the professionals. Leftover

colors should not be disposed of with household waste. You should seek advice from local authorities on the disposal and collection of waste.

Poisoning Information Centre Tel. 210 77.93.777

TECHNICAL CHARACTERISTICS		UNITS	STANDARD	PRICE
Density (20°C)	White	(g/ml)	EN ISO 2811.01-02	1,63 ± 0,05
	Bases P,D			1,42 ± 0,06
Viscosity		(cps)	Brookfield	14.000-2.000
pH			ISO 976-96	8-8,7
Gloss (60°)			EN ISO 2813-99	< 5
Accelerated aging by UV radiation (2000h)		(°C)	ISO 11507-97	There is no alteration of gilm
Dilute with water		(% etc.)	-	5-10
Minimum application temperature		(°C)	ELOT 788-85	10

*Note:* Measurements are done in a laboratory environment temperature +230 C, RH 50%, and without aeration. There is the possibility to vary depending on the conditions at the site such as temperature, humidity, ventilation and absorbency of the substrate.

The technical information and instructions in this brochure relating to the application and end-use of products based on Thrakon up this expertise and experience of the products are given in good faith when properly stored, handled and applied in accordance with the instructions of Thrakon. Due to the inability to directly inspect the conditions at the construction site and the implementation process of the product, the Company makes no guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility which is based on quoted information in this booklet, written or oral or otherwise provided recommendations and instructions. Users are advised to perform a little test the product's suitability for the intended application and purpose. Thrakon reserves the right to change the properties of its products without prior notice. All orders are accepted only after the acceptance of the above and under the current terms of trade policy of the Company. The edition of this technical datasheet automatically cancels any previous one.