

STATUS 100% ACRYLIC PUTTY ACRYLIC SPATULA PUTTY



DESCRIPTION

STATUS 100% ACRYLIC PUTTY is a white putty for interior and exterior use that is used in constructions. Can be used for grouting or spatula coating of every plaster, wood, concrete, plasterboard surface, etc., and is ideal for minor grouting works. Easily workable and soft,

does not run and fills evenly. Dries quickly without cracks and is sanded easily, leaving a smooth and highly durable surface. It has strong adhesion, elasticity and resistance to ultraviolet radiation, humidity and frost.

AREAS OF APPLICATION

Suitable for filling and coating both interior and exterior areas. Applied to walls and ceilings, plaster, wood, concrete, plasterboards, etc. It is also suitable for

application where high tolerance is required for crack and joint shrinkage-expansions between structural elements.

ADVANTAGES - SPECIFICATIONS

- Does not crack or form crevices.
- Does not shrink.
- Strong adhesion on all structural substrates.
- Suitable for interior and exterior use.
- Easy to apply, does not run.
- Results in extremely smooth surfaces.
- Resistance to moisture and frost.
- Environmentally friendly.

SUBSTRATE PREPARATION

The surface must definitely be strong, dry and free from dust, oil, lime, salts, loose materials, rust, blistered paint, molds, etc., to ensure good adhesion. Cracks are cleaned

and any loose materials are removed. Surfaces with loose plaster are sanded down and primed with **WATER-BASED STATUS DUR**, diluted 100% with clean water.

APPLICATION

Apply putty with a metal spatula without dilution. Applied in 1-2 layers to a thickness of 0.5-1mm. The second layer is applied after the first has dried. Sand down the surface with sandpaper 1-2 hours after application and dust well. Prime with suitable primer

depending on the final surface. Close the container tightly after use to keep the paint in good condition for future use. Can be stored in a tightly sealed container for a long time.

DRYING

Dries in 1-2 hours.

REQUIRED QUANTITIES

On properly prepared surfaces depending on the application.

STATUS 100% ACRYLIC PUTTY ACRYLIC SPATULA PUTTY



TOOLS

Metallic spatula.

TOOL CLEANING

Clean all tools immediately after use with warm water and soap.
Do not dispose of washing waste water into the aquifer.

PACKAGING

Available in 400gr, 800gr and 5kg plastic containers.

STORAGE

Store original, sealed containers in dry place at temperatures between +5°C and +35°C for a long period of time.

TEMPERATURE

Do not apply when temperatures are below 5°C. Adverse conditions during or shortly after application may affect

the final properties of the product.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining

product should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

Poisons Information Call Center 210 77.93.777

TECHICAL SPECIFICATIONS

UNITS

STANDARD

VALUE

Form			Pasty
Shade			White
Density (20°C)	(g/ml)	EN ISO 2811.01-02	1.80 ± 0.03
Viscosity	cps		300000 ± 40000
Painting after	h		2 - 3

Note: Measurements are performed in a laboratory environment at a temperature of +23°C, a Relative Humidity (RH) of 50% and without ventilation. Variations are possible depending on the work site conditions, such as temperature, humidity, ventilation and absorbcency of the substrate.

The technical information and guidelines in this brochure relating to the application and end-use of Thrakon's products is based on the Company's current expertise and experience on the products and are given in good faith provided they are properly stored, used and applied in accordance with the guidelines given by Thrakon.. Given that we are unable to directly inspect the conditions that prevail at the work site as well as the application of the product, the Company shall not provide any guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility, which is based on written information in this brochure, written or oral or otherwise provided recommendations and guidelines. By applying the product is a small area, users are advised to test the product's suitability for the intended application and purpose. Thrakon reserves the right to amend the properties of its products without prior notice. All orders are accepted only after acceptance of the above and under the Company's respective Trade Policy terms. This version of the technical data sheet automatically cancels any previous version.