

STATUS BASEWOOD PRESERVATIVE WOOD PRIMER



DESCRIPTION

STATUS BASEWOOD is a colourless substrate preservative suitable for preparing wooden surfaces before they are varnished. Suitable for indoor and mainly outdoor use, it can be applied on all wooden surfaces, such as doors, windows, casings, coverings, beams, roofs, enclosures, trellises, garden furniture, etc.

The advanced composition protects the wood effectively from fungi, dry rot, blue stains and mould. It also penetrates deep into the pores of the wood, offering a uniform surface to the final varnish, while its elasticity increases the resistance of the surface to cracking and peeling.

APPLICATION FIELDS

- Applied on all wooden surfaces, such as doors, windows, casings, coverings, beams, roofs, enclosures, trellises, etc.
- Suitable for both indoor and outdoor use.

ADVANTAGES – CHARACTERISTICS

- Protects from humidity and rain.
- Protects from fungi, dry rot, blue stains and mould.
- Protects from ultraviolet (UV) radiation.
- High penetrating property.
- Allows the wood to breathe.
- Follows shrinkage and expansion of the wood and helps the wood avoid cracking and peeling.
- Uniform and exceptional final result.
- Easily worked.
- Exceptionally spread.

SUBSTRATE PREPARATION

The surface should necessarily be dry, rigid and free from dust, mould, grease or resin before application. In new wood, remove any oil or resin with **LS-735 SOLVENT** and then treat the knots. In painted wood, remove the old paints or varnishes with a corrosive medium and then

clean the surface with **LS-735 SOLVENT**. Repair all the defects of the wood with the appropriate stucco. Use the suitable sandpaper to smoothen the surface well in parallel with the texture streaks. Remove dust with a damp, non-fluffy cloth.

APPLICATION

Mix the content of the container before use and apply the product with a brush covering well all difficult points of the surface, such as corners, hollows, etc. After it has dried well, apply 2 layers of the final **STATUS EVERWOOD** wood varnish. Close the

container well so that it can be preserved in good condition for future use. It can be stored in a tightly closed container for a long time, in cool and dry places. Protect the product against sun and frost.

DRYING

Touch dry after 3-4 hours.

RECOATING

Recoat after 8 hours. Drying times refer to normal environmental conditions (25°C, humidity 60%). Any difference in environmental temperature and humidity could affect the above times.

SHADES

Colourless.

APPLICATION RATE

Up to 20 m²/lt, always depending on the feel and absorbability of the wood.

APPLICATION TOOLS

Brush.

CLEANING OF TOOLS

Immediately after use clean the brush or the roller with WHITE SPIRIT and then with hot water and detergent. Do not pour the washing liquids on the ground.

PACKAGING

Available in metal containers of 750ml, 2,5lt.

STORAGE

In the original sealed container, in dry places and at temperatures between +5°C and +35°C for 2-3 years after production date.

VOLATILE ORGANIC COMPOUNDS (VOC)

- Maximum permissible VOC content (Directive 2004/42/EC) for “Interior and exterior minimal build woodstains” A/f (SB): 700 gr/lt.
- Maximum VOC content of product ready for use: 695 gr/lt.

APPLICATION TEMPERATURE

Avoid painting at temperatures lower than 5°C or before rain. During application the surface should not be directly exposed to sunlight.

Adverse conditions during or shortly after application could affect the final properties of the product.

The technical information and guidelines in this brochure related to the application and end-use of THRAKON products are based on the Company's current expertise and experience on the products and are given in good faith provided they are properly stored, used and applied in accordance with the guidelines given by THRAKON. Given that we are unable to directly inspect the conditions that prevail at the worksite as well as the application of the product, the Company shall not provide any guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility that is based on written information in this brochure or on written or oral or otherwise provided recommendations and guidelines. By applying the product on a small surface, the users are advised to test the product's suitability for the intended application and purpose. THRAKON reserves the right to amend the properties of its products without prior notice. All orders are accepted only after acceptance of the above and under the Company's respective Trade Policy terms. This version of the technical data sheet automatically cancels any previous version.

STATUS BASEWOOD

WOOD PRESERVATIVE PRIMER



PRECAUTIONS

For information about safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product, which is available upon request to the professionals.

The remains of the paints should not be disposed of together with domestic waste. Ask for advice from the local government with regard to the disposal and removal of waste.

Poisoning Centre Tel. No.: +30 210 77.93.777

TECHNICAL CHARACTERISTICS	UNITS	STANDARD	VALUE
Density (20°C)	(g/ml)	EN ISO 2811.01-02	0.84 ± 0.02
Viscosity	(sec)	Flow Cup N°4	11 ± 1
Dilution			Ready for use

Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative Humidity 50 % and without ventilation. They may vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation and absorbability of the substrate.