

STATUS ECOVARN **ECOLOGICAL COLOURLESS WATER- SOLUBLE VARNISH**



DESCRIPTION

STATUS ECOVARN is an ecological colourless water-soluble varnish. It protects and also decorates each wooden surface indoors and outdoors. It is odourless, highly efficient and easily applied. Thanks to the built-in filters against ultraviolet radiation, the surface remains

flexible and fully protected even under adverse weather conditions. It is also recommended as final coating for the protection of decorative effects as it does not yellow. The result is a splendid, particularly durable surface that remains inalterable for a long time.

SUBSTRATE PREPARATION

Surfaces must be clean and free of dirt, dust, grease, resin and thoroughly rubbed down with a suitable abrasive paper. On new or bare surfaces, first apply a coat of **STATUS BASEWOOD**. Next apply 1-2 coats of

STATUS ECOVARN. For maintenance of already varnished surfaces, sand the surface lightly with fine abrasive paper and apply 1 coat of **STATUS ECOVARN**.

APPLICATION TIPS

If you use brush, preferably apply in the direction of the natural wood patterns. Sand surface lightly with very fine abrasive paper. Dust thoroughly between coats. Wood humidity must remain at a low level.

CLEANING TOOLS

Immediately after use strain well all your tools from paint back to the pot and clean all tools with water and soap. Avoid washing materials entering into watercourses.

STORING

Close well after application. It can be stored in tightly closed container without any problem for a long time only if it has not been diluted. Store in a cool and dry place. Protect the container from sun exposure and frost. The remaining paint must not be emptied with household waste. The local authority must be contacted for advice about the disposal and waste collection. Poison centre line: 2107793777. For more information about the reasons this product has been awarded the eco label please visit the website www.ecolabel.eu.

APPLICATION METHOD-SPREADING RATE

Brush, roller, gun or airless gun. 12-14 m²/lt on surfaces properly prepared.

RESTRICTIONS

Do not apply at temperatures below 10°C. Adverse conditions during or shortly after application may affect the final properties of the product.

DRYING - REPAINTING

½-1 hour's touch free. Recoatable after 2-3 hours, depending on the temperature and humidity of the environment. Drying times are related to standard weather conditions (25°C, 60% humidity). These can be changed under different weather conditions.

TECHNICAL CHARACTERISTICS	UNITS	STANDARD	VALUE
Density (20°C)	(g/ml)	EN ISO 2811.01-02	1,04 ± 0,03
Viscosity	(cps)	Brookfield	20.000-30.000
Dilute with water (optional)	(%)		5-10

Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50 % and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.