

STATUS KITCHEN & BATH ANTIMOULD EMULSION PAINT



DESCRIPTION

STATUS KITCHEN & BATH is a top-quality emulsion paint ideal for application on indoor surfaces that have problems with the growth of mould and fungi, such as kitchens, bathrooms, ceilings, storerooms, etc. The special fungicide substances contained in the product prevent the growth of mould and bacteria, thus constituting an ideal solution for places such as pharmaceutical industries, food industries, operating

theatres and accommodation facilities. It is odourless, ammonia-free and absolutely user and environmental friendly. Easily applied and perfectly spread, it covers everything and is highly effective. The result is a perfectly matt surface that shows tolerance to frequent washing with detergents or disinfectants and maintains its beautiful appearance for a long time.

APPLICATION FIELDS

- Suitable for application on indoor surfaces that have problems with the growth of mould and fungi, such as kitchens, bathrooms, ceilings, storerooms, etc.
- Ideal solution for places such as pharmaceutical industries, food industries, operating theatres and accommodation facilities.
- Applied on new or painted surfaces on which the suitable preparation, such as plaster, concrete, bricks, gypsum boards, wood, walls, has been previously applied.

ADVANTAGES – CHARACTERISTICS

- Environmental friendly product without solvents.
- High protection from mould and fungi
- Odourless
- Ammonia-free.
- Resistant to washing.
- Perfect coverage.
- Resistance to detergents and disinfectants.
- Suitable for application in pharmaceutical industries, food industries, operating theatres and accommodation facilities.
- Perfectly worked.
- Excellent spreading.
- High performance.

SUBSTRATE PREPARATION

The surface should necessarily be clean, dry, rigid and free from dust, mould and oil before application. Remove all detached or peeled old paints. If stucco is required, use **STATUS 100% ACRYLIC STUCCO** and after it dries, sandpaper and dust well. In big cracks use the Light, White ready for use **STATUS ONE COVER** acrylic putty. Apply only one layer and do not smooth. In new surfaces, first apply a layer of **STATUS ACRYLIC PRIMER**, or **STATUS DUR WATER BASED**

PRIMER. If the plaster is fresh or cement, let necessarily dry in depth for at least 1 month before the application of the paint. In gypsum boards and in case of surfaces recoated with water paints (with lime or adhesive) or dirty faces (nicotine, smog from radiators, smut, exhaust fumes, coffee, juice, graffiti, ink, markers, fungi, mould, humidity, oil, etc.), first apply **STATUS DUR** primer

APPLICATION

Mix well the content of the container before use, dilute properly and apply 1-2 layers of paint. Apply the second layer at least 2-3 hours after the first. After application, close the container tightly to maintain in good condition for future use. It can be stored in a tightly closed container for a long time as long as it has not been diluted. Painted surfaces should not be washed before

20-30 days have passed after painting. In new surfaces from plaster or concrete, the paint should be applied after 30-40 days.

STATUS bases are exclusively used for the production of shades with the help of the **STATUS** colouring system and should not be applied without adding the special **STATUS** pigments. Very dark shades of matt paints that are frequently washed are not recommended.

DRYING

Touch dry after 1 hour.
Full resistance to washing after 4 weeks.

RECOATING

Recoat after 2-3 hours. Drying times refer to normal environmental conditions (25°C, humidity 60%). Any difference in environmental temperature and humidity could affect the above times.

SHADES

Available in white and in thousands of shades through STATUS painting system.

APPLICATION RATE

10-12 m²/lt, depending on the feel and absorbability of the surface.

APPLICATION TOOLS

Brush, roller, or airless gun.

CLEANING OF TOOLS

Immediately after use empty all the paint into the container and clean all the tools with hot water and soap. Do not pour the washing liquids on the ground.

PACKAGING

Available in plastic containers of 0,75 lt, 3 lt, 10 lt.

STORAGE

In the original sealed container, in dry places and at temperatures between +5°C and +35°C for 12 months after production date.

VOLATILE ORGANIC COMPOUNDS (VOC)

- Maximum permissible VOC content (Directive 2004/42/EC) for A/a “Matt indoor walls & ceilings (gloss ≤ 25@60°)” products, Type WB, STAGE II: 30 gr/lt.
- Maximum VOC content in product ready for use: 25 gr/lt.

APPLICATION TEMPERATURE

Avoid painting at temperatures lower than 5°C or before rain. During application the surface should not be directly exposed to solar radiation.

Adverse conditions during or shortly after application could affect the final properties of the product.

The technical information and guidelines in this brochure related to the application and end-use of THRAKON products are based on the Company's current expertise and experience on the products and are given in good faith provided they are properly stored, used and applied in accordance with the guidelines given by THRAKON. Given that we are unable to directly inspect the conditions that prevail at the worksite as well as the application of the product, the Company shall not provide any guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility that is based on written information in this brochure or on written or oral or otherwise provided recommendations and guidelines. By applying the product on a small surface, the users are advised to test the product's suitability for the intended application and purpose. THRAKON reserves the right to amend the properties of its products without prior notice. All orders are accepted only after acceptance of the above and under the Company's respective Trade Policy terms. This version of the technical data sheet automatically cancels any previous version.

STATUS KITCHEN & BATH ANTIMOULD EMULSION PAINT



PRECAUTIONS

For information about safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product, which is available upon request to the professionals.

The remains of the paints should not be disposed of together with domestic waste. Ask for advice from the local government with regard to the disposal and removal of waste.

Poisoning Centre Tel. No.: 210 77.93.777

TECHNICAL CHARACTERISTICS	UNITS	STANDARD	VALUE
Density (20°C)	(g/ml)	EN ISO 2811.01-02	1.52 ± 0.05
Viscosity	(cps)	Brookfield	10,000-20,000
pH		ISO 976-96	8-8.7
Gloss (60°C)		EN ISO 2813-99	< 4
Tolerance to washing-rubbing	(CLASS)	EN ISO 11998-02	2
Accelerated ageing through UV radiation (1000h)	(°C)	ISO 11507-97	No alteration of the film is detected
Dilution with water	(% by volume)	-	5-10

Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative Humidity 50 % and without ventilation. They may vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation and absorbability of the substrate.