

## STATUS WOOD CLASSIC DECORATIVE WOOD VARNISH



### DESCRIPTION

**STATUS WOOD CLASSIC** is a top quality varnish containing polyurethane, a substance suitable for all indoor or outdoor wooden surfaces.

It offers high resistance and excellent glossy appearance.

### APPLICATION FIELDS

Suitable for all indoor or outdoor wooden surfaces.

### ADVANTAGES – CHARACTERISTICS

- High resistance
- Gloss

### SUBSTRATE PREPARATION – APPLICATION

In order to secure proper adhesion of the varnish, the wood should be free from dust, oil and resin, while it should also have been properly sanded.

In new and unpainted surfaces, first apply a layer of **STATUS BASEWOOD**, which protects the wood from fungi and dry rot. Then smooth lightly and apply 1-2 layers of **STATUS WOOD CLASSIC**.

In old wood, in case the varnish is in bad condition, remove it completely with **REMOVER** and then wash the wood with **LS-735 NITRO SOLVENT**. Apply 1-2 layers of **STATUS WOOD CLASSIC**. In order to preserve-refresh already varnished surfaces, smooth lightly and apply a layer of **STATUS WOOD CLASSIC**.

### APPLICATION

Immediately after dilution stir well for absolute homogenization of the product. The humidity of the wood should be low. Sand very lightly with very thin sandpaper and wipe well before each layer. If you use a brush, work in parallel with the streaks of the texture.

Do not interrupt painting a surface in order to continue later. Complete without intervals. You should know that every new layer of a coloured **STATUS WOOD CLASSIC** darkens the final shade.

## DRYING

Touch dry after 5-6 hours.

## RECOATING

Recoat after 24 hours. Drying times refer to normal environmental conditions (25°C, humidity 60%). Any difference in environmental temperature and humidity could affect the above times.

## SHADES

Available in gloss colourless, satin or matt and in 5 glossy shades of the colour index.

## APPLICATION RATE

8-10 m<sup>2</sup>/lt on properly prepared surfaces.

## APPLICATION TOOLS

Brush, roller.

## CLEANING OF TOOLS

Immediately after use clean all the tools with **WHITE SPIRIT** and then with hot water and detergent. Do not pour the washing liquids on the ground.

## PACKAGING

Gloss colourless: 180ml, 750ml, 2.5L.  
Gloss shade: 180ml, 750ml.  
Colourless satin/matt: 750ml, 2.5L.

## STORAGE

After application close the container tightly to preserve in good condition for future use. It can be stored in tightly closed containers for a long time. Store in cool and dry places. Protect from sun and frost.

## VOLATILE ORGANIC COMPOUNDS (VOC)

- Varnishes and impregnating Varnishes for indoor and outdoor use in decorative objects, including opaque impregnating varnishes (SB)
- VOC limit value – Stage II: 400 gr/lt
- Maximum VOC content in product ready for use: 395 gr/lt
- Maximum dilution: 2% by volume

## APPLICATION TEMPERATURE

Avoid painting at temperatures lower than 5°C. Adverse conditions during or shortly after application could affect the final properties of the product.

## PRECAUTIONS

For information about safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product, which is available upon request to the professionals.

The remains of the paints should not be disposed of together with domestic waste. Ask for advice from the local government with regard to the disposal and removal of waste.

Poisoning Centre Tel. No.: 210 77.93.777

*The technical information and guidelines in this brochure related to the application and end-use of THRAKON products are based on the Company's current expertise and experience on the products and are given in good faith provided they are properly stored, used and applied in accordance with the guidelines given by THRAKON. Given that we are unable to directly inspect the conditions that prevail at the worksite as well as the application of the product, the Company shall not provide any guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility that is based on written information in this brochure or on written or oral or otherwise provided recommendations and guidelines. By applying the product on a small surface, the users are advised to test the product's suitability for the intended application and purpose. THRAKON reserves the right to amend the properties of its products without prior notice. All orders are accepted only after acceptance of the above and under the Company's respective Trade Policy terms. This version of the technical data sheet automatically cancels any previous version.*