

## WASH PRIMER EPOXY PRIMER



### DESCRIPTION

**WASH PRIMER** is a 2-component primer based on special synthetic resins intended for ferrous and non-ferrous metal surfaces. It is used for priming mainly non-ferrous surfaces, such as aluminum, copper, zinc and

galvanized steel sheet in order to improve adhesion because it is very difficult to apply a paint directly onto the surface. It also has very good antirust properties and is highly resistant to water.

### APPLICATION FIELDS

Suitable for priming mainly non-ferrous surfaces, such as aluminum, copper, zinc and galvanized steel sheet in

order to improve adhesion because it is very difficult to apply a paint directly onto the surface.

### ADVANTAGES – CHARACTERISTICS

- Very good antirust properties.
- High resistance to water.

### SUBSTRATE PREPARATION – APPLICATION

Mix 4 volumes of component A with 1 volume of component B and dilute up to approximately 20% with LS-702 SOLVENT.

Apply a thin dry film layer 10-15µm thick on the thoroughly cleaned surface with a gun. When it dries, you can apply the desired paint.

### DRYING – RECOATING

- Touch dry after 15-30 minutes.
- Recoat after 6 hours. Drying times refer to normal environmental conditions (25°C, humidity 60%). Any difference in environmental temperature and humidity could affect the above times.

### APPLICATION RATE

14 - 15 m<sup>2</sup>/Kg (for dry film thickness 10 µm).

## WASH PRIMER EPOXY PRIMER



### APPLICATION TOOLS

Gun.

### CLEANING OF TOOLS

Clean with **LS-735 MULTIPURPOSE NITRO SOLVENT**. Do not pour the washing liquids on the ground.

### PACKAGING – SHADES

Component A is available in a plastic container of 800g.  
Component B is available in a plastic container of 200g  
Available in green.

### DILUTION

Mix 4 parts of component A with 1 part of component B and dilute up to approximately 20% with **LS-702 SOLVENT**.

### STORAGE

**WASH PRIMER** can be stored in tightly closed containers for a long time, in cool and dry places.

### PRECAUTIONS

For information about safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product, which is available upon request to the professionals.

The remains of the paints should not be disposed of together with domestic waste. Ask for advice from the local government with regard to the disposal and removal of waste.  
Poisoning Centre Tel. No.: 210 77.93.777

*The technical information and guidelines in this brochure related to the application and end-use of THRAKON products are based on the Company's current expertise and experience on the products and are given in good faith provided they are properly stored, used and applied in accordance with the guidelines given by THRAKON. Given that we are unable to directly inspect the conditions that prevail at the worksite as well as the application of the product, the Company shall not provide any guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility that is based on written information in this brochure or on written or oral or otherwise provided recommendations and guidelines. By applying the product on a small surface, the users are advised to test the product's suitability for the intended application and purpose. THRAKON reserves the right to amend the properties of its products without prior notice. All orders are accepted only after acceptance of the above and under the Company's respective Trade Policy terms. This version of the technical data sheet automatically cancels any previous version.*